

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
16 October 2003 (16.10.2003)

PCT

(10) International Publication Number
WO 03/084529 A1

(51) International Patent Classification⁷: **A61K 31/337, A61P 35/00**

(74) Agent: VAN WERMESKERKEN, Stephanie, C.; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(21) International Application Number: **PCT/IB03/00853**

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: **7 March 2003 (07.03.2003)**

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
02076441.1 11 April 2002 (11.04.2002) EP

(71) Applicant (*for all designated States except US*): **KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).**

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



A1

(54) Title: **LOW-PRESSURE MERCURY VAPOR DISCHARGE LAMP**

(57) **Abstract:** Low-pressure mercury vapor discharge lamp provided with a discharge vessel (10) which encloses enclosing a discharge space (11) provided with a filling of mercury and a rare gas in a gastight manner. The inner wall of the discharge vessel (10) is provided with a transparent layer (16) and a luminescent layer (17). According to the invention, the luminescent layer (17) is provided with a further transparent layer (18). Preferably, both transparent layers (16, 18) comprise an oxide of scandium, yttrium, or a further rare-earth metal, and/or a borate or phosphate of an alkaline-earth metal, and/or of scandium, yttrium, or a further rare-earth metal. Preferably, the alkaline-earth metal is calcium, strontium, and/or barium. The further rare-earth metal is preferably lanthanum, cerium, and/or gadolinium. The oxide is preferably Y₂O₃ or Gd₂O₃. The lamp according to the invention has a comparatively low mercury consumption.

WO 03/084529